

FLASH TUBE, All Sizes & Colors

INSTRUCTIONS FOR USE

WARNING! Not for consumer use.

RES Specialty Pyrotechnics Inc. products are for professional use only by licensed operators familiar with the use of these products. User assumes all liability. User is responsible for use, storage and transportation in compliance with all local, state and federal laws. Misuse may result in injury and damage to property. Refer to our <u>Safety Guidelines</u> sheet for further information.

DISCLAIMER

RES Specialty Pyrotechnics Inc. makes no guarantee or warranty. Our products are sold under the condition that the user will evaluate them to determine suitability for their intended use.

Device Description:

Flash Tubes are pre-loaded pyrotechnic devices that produce a white or colored flash of light and a puff of smoke. White Bang has noise and White Bang Spark has a spray of sparks along with noise and flash. These devices come with an electric match pre-installed in the device. Color and size are listed on the device label.

Always pay attention to the orientation arrow on each device label. This indicates the direction the effect will be projected.

CAUTION! Flash Tubes must only be fired in the upright position as indicated to function properly.

Flashtubes must have a minimum separation from the audience of at least 15 feet. See NFPA 1126 for additional safety parameters.

Always test fire a Flash Tube in a safe area, preferably outdoors, to become familiar with the performance of the device and to determine if the device can be used safely.

CAUTION! Do not disassemble or modify. Accidental ignition, fire or injury may result!

Always wear safety glasses when handling pyrotechnics!

Do not remove device from plastic bag until just before use. The desiccant in the sealed bag prevents moisture from degrading the product.

SETUP DEVICE

- 1) Disable firing system.
- Place Flash Tube in secure holder paying attention to the orientation arrow on device label. Do not over-tighten set screws as this may damage the device and cause a malfunction.
- Position device so it can function safely.
 Check separation distances from people and flammable objects. Ensure operator can observe device where it is placed.

TEST DEVICE

- 1) Confirm firing system is disabled.
- Connect electric match leads to firing system.
- 3) Ensure device is safe to test. People and property must be at a safe distance should an accidental ignition occur. Warn others in the area that a test is taking place.
- 4) Test circuit according to the firing system manufacturer's instructions.
- 5) Disable firing system after testing.

FIRE DEVICE

- 1) Confirm that device can be fired safely.
- Confirm operator can observe device being fired.
- Enable firing system.
- 4) Fire device according to firing system manufacturer's instructions.
- 5) Disable firing system after firing device.

Additional information and guidelines for the use of proximate pyrotechnics can be found in NFPA 1126: Standard for the use of Pyrotechnics before a Proximate Audience.

RES Specialty Pyrotechnics Inc. is available to answer any questions you may have concerning our products. Please call us Monday through Friday, 8AM until 4PM at: 952-873-3113. You may also e-mail us at: info@respyro.com.