

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Flash Tube

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Pyrotechnic Article

1.3. Details of the supplier of the safety data sheet

RES Specialty Pyrotechnics, Inc. 21595 286th Street Belle Plaine, MN 56011

1.4. Emergency telephone number

Emergency number : 952-873-3113

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Expl. 1.4 H204 Flam. Sol. 2 H228 Ox. Sol. 3 H272 Acute Tox. 4 (Oral) H302 Skin Sens. 1 H317

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS01

GHS02





Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H204 - Fire or projection hazard

H228 - Flammable solid

H272 - May intensify fire; oxidizer H302 - Harmful if swallowed

H317 - May cause an allergic skin reaction

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P220 - Keep/Store away from clothing/combustible materials P221 - Take any precaution to avoid mixing with combustibles P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P250 - Do not subject to grinding/shock/friction

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P312 - If swallowed: Call a poison center/doctor if you feel unwell

P302 + P352 - If on skin: Wash with plenty of water

P330 - Rinse mouth

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use water to extinguish

P370+P380 - In case of fire: Evacuate area

P372 - Explosion risk in case of fire

P373 - DO NOT fight fire when fire reaches explosives

P374 - Fight fire with normal precautions from a reasonable distance

P401 - Store locked up

P501 - Dispose of contents/container in accordance with local/regional/national/international

06/12/2015 EN (English US) Page 1

Safety Data Sheet

regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Pyrotechnic mixtures in solid form containing fuels and oxidizers, pyrotechnic substances or a mixture of substances designed to produce an effect by heat, light, sound, gas, or smoke or a combination of these as the result of non-detonative self-sustaining exothermic chemical reactions. These items are classified as explosives 1.4G by the U.S. DOT. No chemical composition is exposed during normal handling, transportation and storage. The following components are present in these products as a pyrotechnic composition:

Name	Product identifier	%	Classification (GHS-US)
Magnesium	(CAS No) 7439-95-4	0 - 84.8	Not classified
Aluminum	(CAS No) 7429-90-5	0 - 84.8	Not classified
Strontium nitrate	(CAS No) 10042-76-9	0 - 40	Not classified
Barium nitrate	(CAS No) 10022-31-8	0 - 40	Acute Tox. 4 (Oral), H302
Potassium nitrate	(CAS No) 7757-79-1	0 - 20	Ox. Sol. 3, H272 Aquatic Acute 3, H402
Titanium	(CAS No) 7440-32-6	0 - 20	Not classified
1,3,5,7-Tetraazatricyclo[3.3.1.13,7]decane	(CAS No) 100-97-0	0 - 10	Not classified
Vinyl chloride-vinylidene chloride copolymer	(CAS No) 9011-06-7	0 - 10	Not classified
Ethanedioic acid, disodium salt	(CAS No) 62-76-0	0 - 10	Not classified
Carbon black	(CAS No) 1333-86-4	0 - 4	Not classified
Sulfur	(CAS No) 7704-34-9	0 - 3	Skin Irrit. 2, H315

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1.	Docorine	ion of	firet aid	measures
4.1.	Describi	101101	III St alu	IIIeasures

First-aid measures after inhalation

: Medical attention is required. Remove to fresh air. Professional assistance by a doctor is needed if irritation develops or persists.

First-aid measures after skin contact

: No immediate medical attention is required. Remove contaminated clothing as needed and launder before reuse. Wash skin thoroughly with mild soap/water. Professional assistance by a doctor is needed if irritation develops or persists.

First-aid measures after eye contact

: Medical attention is required. Immediately flush eyes with plenty of water for 15 minutes. An eye wash kit is required at the workplace. Professional assistance by a doctor is needed if irritation persists.

First-aid measures after ingestion

: Medical attention is required. Professional assistance by a doctor is needed. Induce vomiting immediately (as directed by medical personnel). Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: Not anticipated under normal use conditions. If casing is broken, dusts may cause irritation.

Symptoms/injuries after skin contact

: Not anticipated under normal use conditions. If casing is broken, dusts may cause irritation.

Symptoms/injuries after eye contact Symptoms/injuries after ingestion : Not anticipated under normal use conditions. If casing is broken, dusts may cause irritation.

: Not anticipated under normal use conditions. If casing is broken, ingested dusts may cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Pyrotechnics are self oxidizing. Flood with water. Fire extinguisher (Class A) may be used. Do not use suffocation methods.

Unsuitable extinguishing media

: None.

06/12/2015 EN (English US) 2/9

Safety Data Sheet

5.2. Special hazards arising from the substance or mixture

Fire hazard : May cause fire or explosion; strong oxidizer.

Explosion hazard : These products will burn rapidly in the event of a fire. Fiery debris may be projected. Large

quantities may explode in a fire.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Spille

: Spilled composition is highly combustible. In case a device is broken open and pyrotechnic composition is spilled: Keep away any possible ignition source such as open flames, sparks and lit cigarettes. Prevent possible electrostatic discharges (for example: do not use a synthetic

dustpan and brush).

Methods for cleaning up

: Carefully pick up the material and place in a cardboard container. For dusts which may be released from a broken device, use dustless methods and place into a closed container for disposal. Take up wet and do not dry sweep or blow with compressed air. Care must be taken when using or disposing of chemical materials and/or their containers to prevent environmental contamination.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: All pyrotechnic devices should be handled with caution. Avoid open flames, smoking, friction, impact, excessive heat, electrostatic discharges, radio frequent interference and moisture.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Pyrotechnics

SECTION 8: Exposure controls/personal protection

3.1. Control parameters

Strontium nitrate (10042-76-9)	
ACGIH	Not applicable
OSHA	Not applicable

Potassium nitrate (7757-79-1)	
ACGIH	Not applicable
OSHA	Not applicable

Magnesium (7439-95-4)	
ACGIH	Not applicable
OSHA	Not applicable

Aluminum (7429-90-5)		
ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (respirable fraction)
OSHA	` , ` • ,	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)

06/12/2015 EN (English US) 3/9

Safety Data Sheet

Vinyl chloride-vinylidene chloride copolymer (9011-06-7)			
ACGIH	Not applicable		
OSHA	Not applicable	11	
1,3,5,7-Tetraazatric	yclo[3.3.1.13,7]decane (100-97-0)		
ACGIH	Not applicable		
OSHA	Not applicable		
Sulfur (7704-34-9)			
ACGIH	Not applicable		
OSHA	Not applicable		
Carbon black (1333	-86-4)		
ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (inhalable fraction)	
OSHA	OSHA PEL (TWA) (mg/m³)	3.5 mg/m ³	
Barium nitrate (100	22-31-8)		
ACGIH	Not applicable		
OSHA	Not applicable	Not applicable	
Titanium (7440-32-6	Titanium (7440-32-6)		
ACGIH	Not applicable		
OSHA	Not applicable		
Ethanedioic acid, d	Ethanedioic acid, disodium salt (62-76-0)		
ACGIH	Not applicable		
OSHA	Not applicable		

8.2. Exposure controls

Relative vapor density at 20 °C

Relative density

Solubility

Appropriate engineering controls

: None required under normal product handling conditions.

Hand protection

: None required under normal product handling conditions.

Eye protection

: None required under normal product handling conditions.

Skin and body protection

: Wear suitable working clothes.

Respiratory protection : None required under normal product handling conditions.

Physical state	: Solid
Appearance	: Contained in cardboard casing.
Odor	: None
Odor threshold	: Not Applicable
pH	: Not Applicable
Relative evaporation rate (butyl acetate=1)	: Not Applicable
Melting point	: Not Applicable
Freezing point	: Not Applicable
Boiling point	: Not Applicable
Flash point	: Not Applicable
Auto-ignition temperature	: >150°C
Decomposition temperature	: Not Applicable
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available

06/12/2015 EN (English US) 4/9

: No data available

: No data available

: Not Applicable

Safety Data Sheet

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Open flames, sparks, high temperatures, friction or impact, electrostatic discharges and radio frequent radiation.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Decomposition does not occur under normal circumstances during storage, transport and handling.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Flash Tube	
ATE US (oral)	887.500 mg/kg body weight
Strontium nitrate (10042-76-9)	
LD50 oral rat	2750 mg/kg
Potassium nitrate (7757-79-1)	
LD50 oral rat	3015 mg/kg
ATE US (oral)	3015.000 mg/kg body weight
Magnesium (7439-95-4)	
LD50 oral rat	230 mg/kg

1,3,5,7-Tetraazatricyclo[3.3.1.13,7]decane (100-97-0)	
LD50 oral rat	9200 mg/kg
ATE US (oral)	9200.000 mg/kg body weight
Sulfur (7704-34-9)	
LD50 oral rat	> 3000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 9.23 mg/l/4h
Carbon black (1333-86-4)	
LD50 oral rat	> 15400 mg/kg
Barium nitrate (10022-31-8)	
LD50 oral rat	355 mg/kg
ATE US (oral)	355.000 mg/kg body weight

	Ethanedioic acid, disodium salt (62-76-0)	
	LD50 oral rat	11160 mg/kg
_		

06/12/2015 EN (English US) 5/9

Safety Data Sheet

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Vinyl chloride-vinylidene chloride copolymer (9011-06-7)

IARC group 3 - Not classifiable

Carbon black (1333-86-4)

, , , , , , , , , , , , , , , , , , , ,	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

1,3,5,7-Tetraazatricyclo[3.3.1.13,7]decane (100-97-0)			
LC50 fish 1	44600 - 55600 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])		
EC50 Daphnia 1	29868 - 43390 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
Sulfur (7704-34-9)			
LC50 fish 1	866 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])		
LC50 fish 2	< 14 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])		

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

06/12/2015 EN (English US) 6/9

Safety Data Sheet

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international

regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN0431 Articles, pyrotechnic (for technical purposes), 1.4, II

UN-No.(DOT) : UN0431

DOT Proper Shipping Name : Articles, pyrotechnic

for technical purposes

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT) : 1.4G - Explosive

1.4

Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 62

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Packaging Exceptions (49 CFR 173.xxx) : None

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 75 kg

CFR 175.75)

DOT Vessel Stowage Location : 02 - The material may be stowed "on deck" or "under deck" on a cargo vessel (up to 12

passengers) and "on deck" in closed cargo transport units or "under deck" in closed cargo

: 1.4 - Class 1.4 - Explosives (with no significant blast hazard) 49 CFR 173.50

transport units on a passenger vessel.

DOT Vessel Stowage Other : 25 - Shade from radiant heat

SECTION 15: Regulatory information

15.1. US Federal regulations

Strontium nitrate (10042-76-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Potassium nitrate (7757-79-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium (7439-95-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Aluminum (7429-90-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 % (dust or fume only)

Vinyl chloride-vinylidene chloride copolymer (9011-06-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,3,5,7-Tetraazatricyclo[3.3.1.13,7]decane (100-97-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Sulfur (7704-34-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

06/12/2015 EN (English US) 7/9

Safety Data Sheet

Barium nitrate (10022-31-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Titanium (7440-32-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethanedioic acid, disodium salt (62-76-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Carbon black (1333-86-4)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Strontium nitrate (10042-76-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Potassium nitrate (7757-79-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Magnesium (7439-95-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Aluminum (7429-90-5)

- U.S. Massachusetts Right To Know List
- U.S. Minnesota Hazardous Substance List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

1,3,5,7-Tetraazatricyclo[3.3.1.13,7]decane (100-97-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

Sulfur (7704-34-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Carbon black (1333-86-4)

- U.S. Massachusetts Right To Know List
- U.S. Minnesota Hazardous Substance List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Barium nitrate (10022-31-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Titanium (7440-32-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

06/12/2015 EN (English US) 8/9

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases::

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3	
Expl. 1.4	Explosive Category 1.4	
Flam. Sol. 2	Flammable solids Category 2	
Ox. Sol. 3	Oxidizing solids Category 3	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
Skin Sens. 1	Skin sensitization Category 1	
H204	Fire or projection hazard	
H228	Flammable solid	
H272	May intensify fire; oxidizer	
H302	Harmful if swallowed	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H402	Harmful to aquatic life	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/12/2015 EN (English US) 9/9